



Power : 27HP | Drive : 4WD

VT30

TRACTOR

Built to perform reliably in rough terrain, extreme weather,
and continuous workloads.



TREM IIIA
ENGINE



AERODYNAMIC
DESIGN

COBO

CLUSTER

800KG

LIFTING
CAPACITY



WIDER
PLATFORM

STANDARD FEATURES

4WD

ENGINE

Make	MITSUBISHI
Model	MVS3L2
Emission	TREM IIIA
HP / kW	27 / 19.9
No. of Cylinders	3
Bore/Stroke (mm)	78/92
Cubic Capacity (cc)	1318
Rated RPM	2500 ± 30
Air Cleaner	Dry Air Cleaner with Clogging Sensor
Max Torque (Nm @ RPM)	79.0@1400 - 2200
Exhaust	Underhood Downdraft

TRANSMISSION

Drive	4WD
Clutch	Single Clutch
Gearbox	9F + 3R
Transmission Type	Constant Mesh

PTO

PTO (RPM)	540 / 540 E
PTO (actuation)	Mechanically actuated, Hand operated

ELECTRICAL

Battery (V, Ah)	12, 65
Alternator (V, A)	12, 65
Trailer Socket	Yes, Seven Pin (Round)

DCV

DCV	Yes
------------	-----

STEERING

Steering	Power
-----------------	-------

SPEED FORWARD

Min Speed (Km/h) @ rpm	1.54@2700
Max Speed (Km/h) @ rpm	24.40@2700

BRAKES

Brakes	Oil Immersed Disc Brakes
Type of Actuation	Mechanically actuated
Hand Brake	Yes, Hand Operated

HYDRAULICS

3 Point Linkage	CAT1N
Auxiliary Hydraulic Circuit	1DA
Hydraulic Lifting Capacity (kg) hitch point	800

OTHERS

Mechanical Coupling	Swinging Drawbar
Driver Seat	Horizontally adjustable
Fuel Indicator Gauge	Yes
Front Tow Hook	Yes
ROPS	Yes

WEIGHT

Front Weight	Front weight Carrier (Hanging weight optional)
---------------------	---------------------------------------------------

CAPACITY (L)

Fuel Tank	25
Engine Oil	4
Hydraulic + Transmission	17
Front Axle	2.5

DIMENSION & WEIGHT

Weight (kg)	1055
Wheel Base (mm)	1580
Total Length (mm)	2780
Total Width (mm)	1100
Height (mm)	2550 with ROPS
Ground Clearance (mm)	290
Front Track, (mm)	865
Rear Track, (mm)	830

TYRES

Agri Tyre (Standard)	6.00-12 & 8.3x20	Optional
Industrial Tyre (Front, Rear)	23x8.50-12 & 33x15.5-16.5	
Turf Tyre (Front, Rear)	23x8.50-12 & 33x15.5-16.5	
Radial Tyres	6.5/80-12 & 280/70R20	



www.vhmindustries.com



info@vhmindustries.com