




Power : 25HP | Drive : 4WD

VT30HST

TRACTOR

Built to perform reliably in rough terrain, extreme weather,
and continuous workloads.



STAGE V
ENGINE



AERODYNAMIC
DESIGN

COBO

CLUSTER

800KG

LIFTING
CAPACITY

TECHNICAL SPECIFICATIONS

STANDARD FEATURES

4WD

ENGINE

Make	MITSUBISHI
Model	MVS3L2
Emission	Stage V
HP / kW	25 / 18.2
No. of Cylinders	3
Bore/Stroke (mm)	78/92
Cubic Capacity (cc)	1319
Rated RPM	2500 ± 30
Air Cleaner	Dry Air Cleaner with Clogging Sensor
Max Torque (Nm @ RPM)	76.3@2000
Exhaust	Underhood Downdraft

TRANSMISSION

Drive	4WD
Clutch	NA
Gearbox	Hydrostatic
No. of Gears	3 Range (High, Medium, Low)

PTO

PTO Speed-Std	Rear 540 & Mid PTO
PTO RPM @ Engine RPM	540@2502/ Mid PTO -2283@2500

ELECTRICAL

Battery (V, Ah)	12/65
Alternator (V, A)	12/65
Trailer Socket	Yes, Seven Pin (Round)

DIRECTIONAL CONTROL VALVE

DCV	Yes
------------	-----

STEERING

Steering	Power
-----------------	-------

WEIGHT

Front Weight	Front Hanging Weight
---------------------	----------------------

BRAKES

Brakes	Oil Immersed Disc Brakes
Type of Actuation	Mechanically actuated
Hand Brake	Yes, Hand Operated

SAFETY SWITCHES

PTO	Yes
Neutral Safety	Yes
Parking Safety	Yes

HYDRAULICS

3 Point Linkage	CAT1N
Auxiliary Hydraulic Circuit	1DA
Hydraulic Lifting Capacity (kg) hitch point	800

OTHERS

Mechanical Coupling	Swinging Drawbar
Driver Seat	Horizontally adjustable
Fuel Indicator Gauge	Yes
Front Tow Hook	Yes
ROPS	Yes

CAPACITY (L)

Fuel Tank	25
Engine Oil	4
Hydraulic + Transmission	17
Front Axle	2.5

TYRES

Turf Tyre (Standard)	23x8.50-12 & 33x15.5-16.5
Agri Tyre (Optional)	6.00-12 & 8.3x20
Industrial Tyre (Optional)	23x8.50-12 & 33x15.5-16.5
Radial Tyres	6.5/80-12 & 280/70R20

