



Power : 26HP | Drive : 4WD

VT30

HST III A

TRACTOR

Engineered for dependable performance across rugged terrain, harsh weather conditions, and demanding, continuous workloads.

Features

- > High Torque (More Power)
- > Projector Head Lamps
- > Down Draft Exhaust
- > Faster Acceleration
- > Oil Immersed Brakes
- > Fuel Efficient Performance

VT30 HST IIIA

TECHNICAL SPECIFICATIONS

STANDARD FEATURES

4WD

ENGINE

Make / Model	mitsubishi / MVS3L2
HP / kW	26 HP / 19.9 kW
No. of Cylinders	3 / 1318
Bore / Stroke (mm)	78/92
Air Cleaner	Dry Air Cleaner with Clogging Sensor
Max Torque (Nm @ RPM)	79.4 @ 1800

TRANSMISSION

Drive	4WD
Clutch	NA
Gearbox	Hydrostatic
No. of Gears	3 Range (High, Medium, Low)

PTO

Dual Speed	540 / 540 E, Mechanically operated
------------	------------------------------------

ELECTRICAL

Battery (V, Ah)	12 / 65
Alternator (V, A)	12
Trailer Socket	Yes, Seven Pin (Round)

DIRECTIONAL CONTROL VALVE

DCV	Yes, Dual Port
-----	----------------

TYRE

Turf Tyre (Standard)	23x8.50-12 & 33x15.5-16.5
Agri Tyre (Optional)	6.00-12 & 8.3x20
Industrial Tyre (Optional)	23x8.50-12 & 33x15.5-16.5
Radial Tyres	6.5/80-12 & 280/70R20

BRAKES

Brakes	Oil Immersed Disc Brakes
Parking Brake	Yes, Hand Operated

PARKING HYDRAULICS

Automatic Draft control	Yes
-------------------------	-----

OTHERS

ROPS	Optional
------	----------

WEIGHT

Front Weight	Front weight carrier (hanging weight optional)
Rear Weight	No

DIMENSION & WEIGHT

Weight (kg)	1000
Wheel Base (mm)	1365
Total Length (mm)	2710
Total Width (mm)	1170
Height (mm)	1355

