



Power : 27HP | Drive : 4WD

# VT30

## TRACTOR

Built to perform reliably in rough terrain, extreme weather,  
and continuous workloads.



TREM IIIA  
ENGINE



AERODYNAMIC  
DESIGN

COBO

CLUSTER

800KG

LIFTING  
CAPACITY



WIDER  
PLATFORM

## STANDARD FEATURES

4WD

### ENGINE

<b>Make</b>	MITSUBISHI
<b>Model</b>	MVS3L2
<b>Emission</b>	TREM IIIA
<b>HP / kW</b>	27 / 19.9
<b>No. of Cylinders</b>	3
<b>Bore/Stroke (mm)</b>	78/92
<b>Cubic Capacity (cc)</b>	1318
<b>Rated RPM</b>	2500 ± 30
<b>Air Cleaner</b>	Dry Air Cleaner with Clogging Sensor
<b>Max Torque (Nm @ RPM)</b>	79.0@1400 - 2200
<b>Exhaust</b>	Underhood Downdraft

### TRANSMISSION

<b>Drive</b>	4WD
<b>Clutch</b>	Single Clutch
<b>Gearbox</b>	9F + 3R
<b>Transmission Type</b>	Constant Mesh

### PTO

<b>PTO (RPM)</b>	540 / 540 E
<b>PTO (actuation)</b>	Mechanically actuated, Hand operated

### ELECTRICAL

<b>Battery (V, Ah)</b>	12, 65
<b>Alternator (V, A)</b>	12, 65
<b>Trailer Socket</b>	Yes, Seven Pin (Round)

### DCV

<b>DCV</b>	Yes
------------	-----

### STEERING

<b>Steering</b>	Power
-----------------	-------

### SPEED FORWARD

<b>Min Speed (Km/h) @ rpm</b>	1.54@2700
<b>Max Speed (Km/h) @ rpm</b>	24.40@2700

### BRAKES

<b>Brakes</b>	Oil Immersed Disc Brakes
<b>Type of Actuation</b>	Mechanically actuated
<b>Hand Brake</b>	Yes, Hand Operated

### HYDRAULICS

<b>3 Point Linkage</b>	CAT1N
<b>Auxiliary Hydraulic Circuit</b>	1DA
<b>Hydraulic Lifting Capacity (kg) hitch point</b>	800

### OTHERS

<b>Mechanical Coupling</b>	Swinging Drawbar
<b>Driver Seat</b>	Horizontally adjustable
<b>Fuel Indicator Gauge</b>	Yes
<b>Front Tow Hook</b>	Yes
<b>ROPS</b>	Yes

### WEIGHT

<b>Front Weight</b>	Front weight Carrier (Hanging weight optional)
---------------------	---

### CAPACITY (L)

<b>Fuel Tank</b>	25
<b>Engine Oil</b>	4
<b>Hydraulic + Transmission</b>	17
<b>Front Axle</b>	2.5

### DIMENSION & WEIGHT

<b>Weight (kg)</b>	1055
<b>Wheel Base (mm)</b>	1580
<b>Total Length (mm)</b>	2780
<b>Total Width (mm)</b>	1100
<b>Height (mm)</b>	2550 with ROPS
<b>Ground Clearance (mm)</b>	290
<b>Front Track, (mm)</b>	830
<b>Rear Track, (mm)</b>	865

### TYRES

<b>Agri Tyre (Standard)</b>	6.00-12 & 8.3x20	Optional
<b>Industrial Tyre (Front, Rear)</b>	23x8.50-12 & 33x15.5-16.5	
<b>Turf Tyre (Front, Rear)</b>	23x8.50-12 & 33x15.5-16.5	
<b>Radial Tyres</b>	6.5/80-12 & 280/70R20	



[www.vhmindustries.com](http://www.vhmindustries.com)



[info@vhmindustries.com](mailto:info@vhmindustries.com)